



Specifications



	Cine 75 HD Film/HD	Studio 9+9 Film/HD	Cine 30 HD Film/HD	Cine 7+7 HD Film/HD	Dutch Head 35 Film/HD
Code	7502	6002	3006	1910	3004
Weight	11.9 kg / 26.2 lbs	8.4 kg / 18.5 lbs	5.6 kg / 12.3 lbs	3.3 kg / 7.3 lbs	6.0 kg / 13.2 lbs
Payload	4-75 kg / 9-165 lbs	8-55 kg / 18-121 lbs	3-35 kg / 7-77 lbs	2-22 kg / 4-48 lbs	0-50 kg / 0-110 lbs
Balance plate / Sliding range	120 mm / 4.7"	115 mm / 4.5"	150 mm / 5.9"	150 mm / 5.9"	60 mm / 2.4"
Counterbalance steps	24 + Boost Button	18	18 + Boost Button	16 + Boost Button	7
Grades of drag					
horizontal steps	9 + 0	9 + 0	7 + 0	7 + 0	
vertical steps	9 + 0	9 + 0	7 + 0	7 + 0	7 + 0 (diagonal)
Tilt range	+90°/-60°	+90°/-60°	+90°/-75°	+90°/-80°	±60°
Temperature range	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F
Camera fitting					
Touch & Go plate	35	35	—	—	35
Sideload plate	—	—	30 HD	M	—
V-plate	—	—	—	—	—
Tripod/Pedestal fitting					
Bowl	150 mm	150 mm	150 mm	100 mm	For fluid heads with Touch & Go plate 35
Mitchell (with adapter)	•	•	•	—	—
Flat Base	Integrated	Integrated	Integrated	—	—
Pan bar(s)					
Type	Movie	Movie	HD	HD	Plus
Number	1	1	1	1	1
telescopic	•	•	•	•	•
Attachment (front/rear/handle)	Ø 20/25/32 mm Ø 0.8/1/1.3"	Ø 20/25/32 mm Ø 0.8/1/1.3"	Ø 18/22/36 mm Ø 0.7/0.9/1.4"	Ø 18/22/36 mm Ø 0.7/0.9/1.4"	Ø 18/22/32 mm Ø 0.7/0.9/1.3"
Length	430-600 mm 16.9-23.6"	430-600 mm 16.9-23.6"	350-520 mm 13.8-20.5"	350-520 mm 13.8-20.5"	350-520 mm 13.8-20.5"
Adapter viewfinder extension / adapter block					
standard	•	•	•	•	—
optional	—	—	—	—	—
Level					
Self-illuminating Touch Bubble	•	•	•	•	—
Batteries 3 x 625 U or LR9	•	•	•	—	—
Battery 1 x CR 2032	—	—	—	•	—
Systems			30 EFP 2 MCF Cine 30	7+7 HD MCF 7+7 ENG 2 CF	

	Video 90 FB Studio / EFP / OB	Video 75 Plus Studio Studio / OB	Video 75 Plus EFP EFP / OB	Video 60 Plus Studio Studio / OB	Video 60 Plus EFP EFP / OB	Video 25 Plus FB Studio / OB
Code	8092	7501	7500	6001	6000	2501P
Weight	14.2 kg / 31.3 lbs	12.9 kg / 28.4 lbs	11.9 kg / 26.2 lbs	9.4 kg / 20.7 lbs	8.4 kg / 18.5 lbs	4.5 kg / 9.9 lbs
Payload	0-115 kg / 0-254 lbs	12-85 kg / 26-187 lbs	12-85 kg / 26-187 lbs	16-65 kg / 35-143 lbs	16-65 kg / 35-143 lbs	8-35 kg / 18-77 lbs
Balance plate / Sliding range	180 mm / 7.1"	145 mm / 5.7"	120 mm / 4.7"	120 mm / 4.7"	115 mm / 4.5"	100 mm / 3.9"
Counterbalance steps	24	24 + Boost Button	24 + Boost Button	18	18	18
Grades of drag						
horizontal steps	7 + 0	9 + 0	9 + 0	9 + 0	9 + 0	7 + 0
vertical steps	7 + 0	9 + 0	9 + 0	9 + 0	9 + 0	7 + 0
Tilt range	+60°/-45°	+80°/-60°	+90°/-60°	+90°/-60°	+90°/-60°	+90°/-75°
Temperature range	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F
Camera fitting						
Touch & Go plate	—	—	35	—	35	35
Sideload plate	—	—	—	—	—	—
V-plate	•	•	—	•	—	—
Tripod/Pedestal fitting						
Bowl	—	150 mm *	150 mm	150 mm *	150 mm	150 mm *
Mitchell (with adapter)	—	—	•	—	—	—
Flat Base	•	•	Integrated	•	Integrated	•
Pan bar(s)						
Type	Pan bar front sections	Pan bar front sections	Pan bar front/rear sections	Pan bar front sections	Plus	Plus
Number	2	2	2 + 2	2	2	2
telescopic	—	—	•	—	•	•
Attachment (front/rear/handle)	Ø 28.5/-/- mm Ø 1.1"/-/-	Ø 28.5/-/- mm Ø 1.1"/-/-	Ø 28.5/35/40 mm Ø 1.1/1.4/1.6"	Ø 28.5/-/- mm Ø 1.1"/-/-	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/22/32 mm Ø 0.7/0.9/1.3"
Length	400 mm 15.7"	400 mm 15.7"	540-720 mm 21.3-28.3"	400 mm 15.7"	350-520 mm 13.8-20.5"	350-520 mm 13.8-20.5"
Adapter viewfinder extension / adapter block						
standard	•	—	•	—	•	—
optional	—	—	—	—	—	—
Level						
Self-illuminating Touch Bubble	•	•	•	•	•	•
Batteries 3 x 625 U or LR9	—	•	•	•	•	•
Battery 1 x CR 2032	—	—	—	—	—	—
Systems						25 Studio 25 Combi 1-40 25 C III

* requires ball adapter with screw



Specifications



	Video 25 Plus EFP / OB	Video 20 S1 EFP / ENG	Video 18 S1 ENG	Video 15 SB ENG	DV 12 SB ENG
Code	2500P	2010	1810	1505	1205
Weight	4.5 kg / 9.9 lbs	3.4 kg / 7.5 lbs	3.3 kg / 7.3 lbs	2.8 kg / 6.2 lbs	2.7 kg / 6.0 lbs
Payload	8–35 kg / 18–77 lbs	2–25 kg / 4–55 lbs	2–18 kg / 4–40 lbs	1–16 kg / 2–35 lbs	1–14 kg / 2–30 lbs
Balance plate / Sliding range	110 mm / 4.3"	120 mm / 4.7"	120 mm / 4.7"	70 mm / 2.8"	70 mm / 2.8"
Counterbalance steps	18	16 + Boost Button	16 + Boost Button	12	12
Grades of drag					
horizontal steps	7 + 0	7 + 0	7 + 0	7 + 0	5 + 0
vertical steps	7 + 0	7 + 0	7 + 0	7 + 0	5 + 0
Tilt range	+90°/-75°	+90°/-70°	+90°/-70°	+90°/-75°	+90°/-75°
Temperature range	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F
Camera fitting					
Touch & Go plate	16	16	16	16	16
Sideload plate S	—	—	—	—	—
Tripod/Pedestal fitting					
Bowl	150 mm	100 mm	100 mm	100 mm	100 mm
Flat Base	Integrated	—	—	Integrated	Integrated
Pan bar(s)					
Type	Plus	Plus	Plus	DV right	DV 100
Number	2	1	1	1	1
telescopic	•	•	•	•	—
Attachment (front/rear/handle)	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/-/32 mm Ø 0.7/-/1.3"
Length	350–520 mm 13.8–20.5"	350–520 mm 13.8–20.5"	350–520 mm 13.8–20.5"	350–520 mm 13.8–20.5"	450 mm 17.7"
Adapter viewfinder extension / adapter block					
standard	•	—	—	—	—
optional	—	•	•	•	•
Level					
Self-illuminating Touch Bubble	•	•	•	•	•
Batteries 3 x 625 U or LR9	•	—	—	•	•
Battery 1 x CR 2032	—	•	•	—	—
Systems	25 EFP 2 CF	20 S1 SL HD MCF 20 S1 HD MCF 20 S1 HD CF	18 S1 SL MCF 18 S1 ENG 2 MCF 18 S1 ENG 2 CF	15 SB SL MCF 15 SB ENG 2 MCF 15 SB ENG 2 CF	12 SB SL MCF 12 SB ENG 2 CF 12 SB

	Video 18 Dutch EFP / ENG	DV 10 SB ENG	FSB 8 HDV / DSLR	FSB 8 T HDV	FSB 6 HDV / DSLR	FSB 6 T HDV
Code	1804	1006	0707	0705	0407	0405
Weight	2.6 kg / 5.7 lbs	2.6 kg / 5.7 lbs	2.15 kg / 4.7 lbs	2.3 kg / 5.1 lbs	2 kg / 4.4 lbs	2.15 kg / 4.7 lbs
Payload	0–18 kg / 0–40 lbs	1–12 kg / 2–26 lbs	1–9 kg / 2–20 lbs	1–9 kg / 2–20 lbs	1–6 kg / 2.2–13.2 lbs	1–6 kg / 2.2–13.2 lbs
Balance plate / Sliding range	60 mm / 2.4"	60 mm / 2.4"	120 mm / 4.7"	60 mm / 2.4"	120 mm / 4.7"	60 mm / 2.4"
Counterbalance steps	5	12	10	10	10	10
Grades of drag						
horizontal steps	7 + 0 (diagonal)	5 + 0	5 + 0	5 + 0	3 + 0	3 + 0
vertical steps	±80°	5 + 0	5 + 0	5 + 0	3 + 0	3 + 0
Tilt range	+90°/-70°	+90°/-70°	+90°/-75°	+90°/-70°	+90°/-75°	+90°/-70°
Temperature range	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F
Camera fitting						
Touch & Go plate	16	5	—	5	—	5
Sideload plate S	—	—	•	—	•	—
Tripod/Pedestal fitting						
Bowl	For fluid heads with Touch & Go plate 16	100 mm	75 mm	75 mm	75 mm	75 mm
Flat Base	—	Integrated	Integrated	Integrated	Integrated	Integrated
Pan bar(s)						
Type	Plus	DV 100	DV 75	DV 75	DV 75	DV 75
Number	1	1	1	1	1	1
telescopic	•	—	—	—	—	—
Attachment (front/rear/handle)	Ø 18/22/32 mm Ø 0.7/0.9/1.3"	Ø 18/-/32 mm Ø 0.7/-/1.3"	Ø 16/-/28 mm Ø 0.6/-/1.1"	Ø 16/-/28 mm Ø 0.6/-/1.1"	Ø 16/-/28 mm Ø 0.6/-/1.1"	Ø 16/-/28 mm Ø 0.6/-/1.1"
Length	350–520 mm 13.8–20.5"	450 mm 17.7"	430 mm 16.9"	430 mm 16.9"	430 mm 16.9"	430 mm 16.9"
Adapter viewfinder extension / adapter block						
standard	—	—	—	—	—	—
optional	—	—	•	•	•	•
Level						
Self-illuminating Touch Bubble	—	•	•	•	•	•
Batteries 3 x 625 U or LR9	—	—	—	—	—	—
Battery 1 x CR 2032	—	•	•	•	•	•
Systems	—	10 SB ENG 2 CF 10 SB	FSB 8 SL MCF FSB 8 / 2 MD FSB 8 MD FSB 8 / 2 D FSB 8	FSB 8 T SL MCF FSB 8 T MD	SOOM FSB 6 FSB 6 SL MCF FSB 6 / 2 MD FSB 6 MD FSB 6 / 2 D FSB 6	FSB 6 T SL MCF FSB 6 T / 2 MD FSB 6 T MD



Specifications

new!



	Cine DSLR HDV / DSLR	FSB 4 HDV / DSLR
Code	0350	0307
Weight	2 kg / 4.4 lbs	1.88 kg / 4.14 lbs
Payload	0,5–5 kg / 1–11 lbs	0–4 kg / 0–9 lbs
Balance plate / Sliding range	120 mm / 4.7"	120 mm / 4.7"
Counterbalance steps	10	5 + 0
Grades of drag		
horizontal steps	3 + 0	3 + 0
vertical steps	3 + 0	3 + 0
Tilt range	+90°/-75°	+90°/-70°
Temperature range	-40°/+60°C -40°/+140°F	-40°/+60°C -40°/+140°F
Camera fitting		
Touch & Go plate	—	—
Sideload plate S	DSLR Plate	•
Tripod/Pedestal fitting		
Bowl	75 mm	75 mm
Flat Base	Integrated	Integrated
Pan bar(s)		
Type	DV 75	DV 75
Number	1	1
telescopic	—	—
Attachment (front/rear/handle)	Ø 16/-/28 mm Ø 0.6"/-/1.1"	Ø 16/-/28 mm Ø 0.6"/-/1.1"
Length	430 mm 16.9"	430 mm 16.9"
Adapter viewfinder extension / adapter block		
standard	—	—
optional	•	—
Level		
Self-illuminating Touch Bubble	•	—
Batteries 3 x 625 U or LR9	—	—
Battery 1 x CR 2032	•	—
Systems	Cine DSLR 2 MD Cine DSLR 2 D	FSB 4 SL MCF FSB 4 / 2 MD FSB 4 MD FSB 4 / 2 D FSB 4